

BRICK® 600

SPECIFICATIONS Ø * <u></u> * Certifications Composition **Average Thickness** Carrier REACH n° 1907/2006/EU Non adhesive PU 600 microns **OEKO-TEX**® Polvester VEGANOK Azienda n. 1004 STANDARD 100

APPLICATION INSTRUCTIONS

⊘ APPLIES ON	SUGGES	red cutting s	ETTINGS	TRANSFER SETTINGS			
cotton, polyester, poly/cotton blends (not suited for treated	▲ Blade	<u></u> Pressure	» Speed	• Time	Jemperature	⊷ Pressure	● Peel
and dye sublimated textiles)	60°	80 gf	10 cm/sec	25 seconds	155°C (311°F)	medium/high (2,5-3,5 bar)	cold

🗹 NOTE: Due to the thickness of the material, we do not recommend cutting details of dimensions less than 0,5 cm

- \rightarrow Mirror cut the design
- \rightarrow Weed excess material
- \rightarrow Place the design on the garment
- \rightarrow Heat apply at the conditions shown above
- \rightarrow Peel carrier cold

PRODUCT HIGHLIGHTS

- \rightarrow Thick product
- ightarrow Adds dimension to any logo
- \rightarrow Matt finish

NOTE: We highly recommend to perform a test, before launching a production!

CARE AND WASHING RECOMMENDATIONS

₩ Washing	A Ironing	🖸 Tumble dry	O Dry cleaning	C Storage Shelf Life	C Storage Temperature	(* Storage Conditions	∮ ⊳ Position
Up to 60°C, best inside-out	YES best inside- out	YES (cotton cycle)	NO	Up to 2 years	Between 18°C and 26°C	Away from sunlight and dust	Vertical

 \rightarrow Wait 24 hours after the application before the first wash

- → Respect the textile recommendations
- → Do not bleach or use aggressive chemical agents

This document can be subject to variations. Updated versions are available on www.siser.com. For further information, please contact our sales office: info@siser.it



Siser s.r.l. Viale della Tecnica, 18 36100 Vicenza - Italy Tel. +39 0444.287960 Fax +39 0444.287959 info@siser.it www.siser.com r.e.a. vi 171856 reg. imp. vi n° 14971 c.s. € 103.300 i.v. p.iva 01591490246

